Image: Non-StateImage: Non-StateImage: Non-StateImage: Non-StateCabinet ColorBlack with hairline texturePanelTFT Active Matrix, LED Backlight 16° Class Widescreen, 16:9 Aspect Ratio 15.6° Viewable Image Size, DiagonalPixel Pitch0.252 x 0.252mmDisplay Area344.2mm x 193.5mmBrightness190 cd/m2 (typ)Contrast Ratio20,000,000:1 (dynamic)Response Time8 msViewing AngleHorizontal: 90 Degrees (CR>10)Vertical: 50 Degrees (CR>10)Scanning FrequencyHorizontal: 30K-60KHzVertical: 60-70 HzPixel Frequency85.5 MHzMaximum Resolution1366x768@60HzSupported Resolutions640x480@60Hz, 1024x768@60Hz, 1024x768@60Hz, 1360x720@60Hz, 1366x768@60HzSignal InputAnalog: 0.7Vp-f(standard), 75 OHM, PositiveConnectorsAnalog RGB Signal: 15-pin D-sub MalePower SourceUSB PoweredPower ConsumptionOn: 7 Watts (Max), Standby: <0.5WPlug & PlayDDC /2B/ClUser ControlPower OnlyOSD Languages15 Languages including English, French and SpanishRegulationsFCC,CE, RoHS, Energy Star 5.0What's in the boxVGA Cable (S-SUB), USB power cable, Instruction Manual, Guarantee Card and Diskette with softwareOther FeaturesUser friendy graphical OSD Menu, eSaver, iMenu and Screen+ Software, ultra low power consumption.Dimensions (WXHxD mm)Monitor: 371x299x143, Carton: 423x304x106 Weight0.87 Kg / 1.92 Ubs (Net) 1.50 Kg / 3.31 lbs (gross)Loading Q	<b>AOC</b> <sup>®</sup> e1670swu	USB Powered Green Monitor
Panel   TFT Active Matrix, LED Backlight 16" Class Widescreen, 16:9 Aspect Ratio 15.6" Viewable Image Size, Diagonal     Pixel Pitch   0.252 × 0.252mm     Display Area   344.2mm x 193.5mm     Brightness   190 cd/m2 (typ)     Contrast Ratio   20,000,000:1 (dynamic)     Response Time   8 ms     Viewing Angle   Horizontal: 90 Degrees (CR>10)     Vertical: 50 Degrees (CR>10)   Vertical: 60-70 Hz     Pixel Frequency   85.5 MHz     Maximum Resolution   1366x768@60Hz     Supported Resolution   1366x768@60Hz     Supported Resolutions   640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1360x720@60Hz, 1366x768@60Hz     Signal Input   Analog: 0.7Vp-p(standard), 75 OHM, Positive     Connectors   Analog RGB Signal: 15-pin D-sub Male     Power Source   USB Powered     Power Consumption   On: 7 Watts (Max), Standby: <0.5W     Plug & Play   DDC / 2B/Cl     User Control   Power Only     OSD Languages   15 Languages including English, French and Spanish     Regulations   FCC,CE, RoHS, Energy Star 5.0     What's in the box   VGA Cable (S-SUB), USB power cable, Instruction Manual, Guarantee Card and Diskette with software	20,000,000:1	
16" Class Widescreen, 16:9 Åspect Ratio     15.6" Viewable Image Size, Diagonal     Pixel Pitch   0.252 x 0.252mm     Display Area   344.2mm x 193.5mm     Brightness   190 cd/m2 (typ)     Contrast Ratio   20,000,000:1 (dynamic)     Response Time   8 ms     Viewing Angle   Horizontal: 90 Degrees (CR>10)     Vertical: 50 Degrees (CR>10)   Vertical: 60-70 Hz     Pixel Frequency   85.5 MHz     Maximum Resolution   1366x768@60Hz     Recommended Resolution   1366x768@60Hz     Supported Resolutions   640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1366x768@60Hz, 1366x76@@60Hz, 1360x720@60Hz, 1366x76@@60Hz, 1024x76@@60Hz, 1366x76@@60Hz, 1366x76@@60Hz, 1366x76@@60Hz, 1024x76@@60Hz, 1366x76@@60Hz, 1366x76@@60Hz, 1366x76@@60Hz, 1366x76@@60Hz, 1024x76@@60Hz, 1360x720@@0Hz, 1366x76@@60Hz, 1024x76@@60Hz, 1360x720@@0Hz, 1366x76@@60Hz, 1024x76@@60Hz, 1360x720@@0Hz, 1366x76@@60Hz, 1024x76@@60Hz, 1360x720@@0Hz, 1366x76@@60Hz, 1024x76@@60Hz, 1366x76@@60Hz, 1366x76@@60Hz, 1360x720@@0Hz, 1366x76@@60Hz, 1024x76@@60Hz, 1360x720@@0Hz, 1360x76@@60Hz, 1360x720@@claz, 1024x76@@60Hz, 150 KW     Supported Resolutions   640x480@@60Hz, 800x600@@60Hz, 1024x76@@60Hz, 1024x76@@claz, 1024x7	Cabinet Color	Black with hairline texture
15.6" Viewable Image Size, Diagonal     Pixel Pitch   0.252 x 0.252mm     Display Area   344.2mm x 193.5mm     Brightness   190 cd/m2 (typ)     Contrast Ratio   20,000,000:1 (dynamic)     Response Time   8 ms     Viewing Angle   Horizontal: 90 Degrees (CR>10)     Scanning Frequency   Horizontal: 30K-60KHz     Vertical: 60-70 Hz   Vertical: 60-70 Hz     Pixel Frequency   85.5 MHz     Maximum Resolution   1366x768@60Hz     Recommended Resolutions   640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1366x768@60Hz     Supported Resolutions   640x480@60Hz, 1366x768@60Hz     Signal Input   Analog: 0.7Vp-p(standard), 75 OHM, Positive     Connectors   Analog RGB Signal: 15-pin D-sub Male     Power Source   USB Powered     Power Consumption   On: 7 Watts (Max), Standby: <0.5W     Plug & Play   DDC /2B/CI     User Control   Power Only     OSD Languages   15 Languages including English, French and Spanish     Regulations   FCC,CE, RoHS, Energy Star 5.0     What's in the box   VGA Cable (S-SUB), USB power cable, Instruction Manual, Guarantee Card and Diskette with software     Other Fe	Panel	TFT Active Matrix, LED Backlight
Pixel Pitch   0.252 x 0.252mm     Display Area   344.2mm x 193.5mm     Brightness   190 cd/m2 (typ)     Contrast Ratio   20,000,000:1 (dynamic)     Response Time   8 ms     Viewing Angle   Horizontal: 90 Degrees (CR>10)     Vertical: 50 Degrees (CR>10)   Vertical: 60-70 Hz     Pixel Frequency   85.5 MHz     Maximum Resolution   1366x768@60Hz     Recommended Resolution   1366x768@60Hz     Supported Resolutions   640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1366x720@60Hz, 1366x768@60Hz     Signal Input   Analog: 0.7Vp-p(standard), 75 OHM, Positive     Connectors   Analog RGB Signal: 15-pin D-sub Male     Power Source   USB Powered     Power Consumption   On: 7 Watts (Max), Standby: <0.5W     Plug & Play   DDC /2B/Cl     User Control   Power Only     OSD Languages   15 Languages including English, French and Spanish     Regulations   FCC,CE, RoHS, Energy Star 5.0     What's in the box   VGA Cable (S-SUB), USB power cable, Instruction Manual, Guarantee Card and Diskette with software     Other Features   User friendly graphical OSD Menu, eSaver, iMenu and Screen+ Software, ultra low power consumption.		16" Class Widescreen, 16:9 Aspect Ratio
Display Area344.2mm x 193.5mmBrightness190 cd/m2 (typ)Contrast Ratio20,000,000:1 (dynamic)Response Time8 msViewing AngleHorizontal: 90 Degrees (CR>10)Vertical: 50 Degrees (CR>10)Scanning FrequencyHorizontal: 30K-60KHzVertical: 60~70 HzPixel Frequency85.5 MHzMaximum Resolution1366x768@60HzRecommended Resolution1366x768@60HzSupported Resolutions640x480@60Hz, 1024x768@60Hz, 1024x768@60HzSignal InputAnalog: 0.7Vp-p(standard), 75 OHM, PositiveConnectorsAnalog RGB Signal: 15-pin D-sub MalePower SourceUSB PoweredPower ConsumptionOn: 7 Watts (Max), Standby: <0.5WPlug & PlayDDC /2B/ClUser ControlPower OnlyOSD Languages15 Languages including English, French and SpanishRegulationsFCC,CE, RoHS, Energy Star 5.0What's in the boxVGA Cable (S-SUB), USB power cable, Instruction Manual, Guarantee Card and Diskette with softwareOther FeaturesUser friendly graphical OSD Menu, eSaver, iMenu and Screen+ Software, ultra low power consumption.Dimensions (WxHxD mm)Monitor: 371x299x143, Carton: 423x304x106 WeightWeight0.87 Kg / 1.92 lbs (Net) 1.50 Kg / 3.31 lbs (gross)		
Brightness   190 cd/m2 (typ)     Contrast Ratio   20,000,000:1 (dynamic)     Response Time   8 ms     Viewing Angle   Horizontal: 90 Degrees (CR>10)     Vertical: 50 Degrees (CR>10)   Vertical: 50 Degrees (CR>10)     Scanning Frequency   Horizontal: 30K-60KHz     Vertical: 60~70 Hz   Pixel Frequency     Pixel Frequency   85.5 MHz     Maximum Resolution   1366x768@60Hz     Supported Resolutions   640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1360x720@60Hz, 1366x768@60Hz     Signal Input   Analog: 0.7Vp-p(standard), 75 OHM, Positive     Connectors   Analog RGB Signal: 15-pin D-sub Male     Power Source   USB Powered     Power Consumption   On: 7 Watts (Max), Standby: <0.5W     Plug & Play   DDC /2B/Cl     User Control   Power Only     OSD Languages   15 Languages including English, French and Spanish     Regulations   FCC,CE, ROHS, Energy Star 5.0     What's in the box   VGA Cable (S-SUB), USB power cable, Instruction Manual, Guarantee Card and Diskette with software     Other Features   User friendly graphical OSD Menu, eSaver, iMenu and Screen+ Software, ultra low power consumption.     Dimensions (WxHxD mm)   Monitor: 371x299x		
Contrast Ratio   20,000,000:1 (dynamic)     Response Time   8 ms     Viewing Angle   Horizontal: 90 Degrees (CR>10)     Vertical: 50 Degrees (CR>10)   Vertical: 30K-60KHz     Vertical: 30K-60KHz   Vertical: 60-70 Hz     Pixel Frequency   85.5 MHz     Maximum Resolution   1366x768@60Hz     Recommended Resolution   1366x768@60Hz     Supported Resolutions   640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1360x720@60Hz, 1366x768@60Hz     Signal Input   Analog: 0.7Vp-p(standard), 75 OHM, Positive     Connectors   Analog RGB Signal: 15-pin D-sub Male     Power Source   USB Powered     Power Consumption   On: 7 Watts (Max), Standby: <0.5W     Plug & Play   DDC /2B/CI     User Control   Power Only     OSD Languages   15 Languages including English, French and Spanish     Regulations   FCC,CE, ROHS, Energy Star 5.0     What's in the box   VGA Cable (S-SUB), USB power cable, Instruction Manual, Guarantee Card and Diskette with software     Other Features   User friendly graphical OSD Menu, eSaver, iMenu and Screen+Software, ultra low power consumption.     Dimensions (WxHxD mm)   Monitor: 371x299x143, Carton: 423x304x106     Weight   0.87		
Response Time   8 ms     Viewing Angle   Horizontal: 90 Degrees (CR>10)     Vertical: 50 Degrees (CR>10)   Scanning Frequency     Horizontal: 30K~60KHz   Vertical: 60~70 Hz     Pixel Frequency   85.5 MHz     Maximum Resolution   1366x768@60Hz     Recommended Resolution   1366x768@60Hz     Supported Resolutions   640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1366x768@60Hz     Signal Input   Analog: 0.7Vp-p(standard), 75 OHM, Positive     Connectors   Analog RGB Signal: 15-pin D-sub Male     Power Source   USB Powered     Power Consumption   On: 7 Watts (Max), Standby: <0.5W     Plug & Play   DDC /2B/Cl     User Control   Power Only     OSD Languages   15 Languages including English, French and Spanish     Regulations   FCC,CE, RoHS, Energy Star 5.0     What's in the box   VGA Cable (S-SUB), USB power cable, Instruction Manual, Guarantee Card and Diskette with software     Other Features   User friendly graphical OSD Menu, eSaver, iMenu and Screen+ Software, ultra low power consumption.     Dimensions (WxHxD mm)   Monitor: 371x299x143, Carton: 423x304x106     Weight   0.87 Kg / 1.92 lbs (Net)     1.50 Kg / 3.31 lbs (gross)   1.50		
Viewing Angle   Horizontal: 90 Degrees (CR>10)     Vertical: 50 Degrees (CR>10)     Scanning Frequency   Horizontal: 30K~60KHz     Vertical: 60~70 Hz     Pixel Frequency   85.5 MHz     Maximum Resolution   1366x768@60Hz     Recommended Resolution   1366x768@60Hz     Supported Resolutions   640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1360x720@60Hz, 1366x768@60Hz     Signal Input   Analog: 0.7Vp-p(standard), 75 OHM, Positive     Connectors   Analog RGB Signal: 15-pin D-sub Male     Power Source   USB Powered     Power Consumption   On: 7 Watts (Max), Standby: <0.5W     Plug & Play   DDC /2B/Cl     User Control   Power Only     OSD Languages   15 Languages including English, French and Spanish     Regulations   FCC,CE, ROHS, Energy Star 5.0     What's in the box   VGA Cable (S-SUB), USB power cable, Instruction Manual, Guarantee Card and Diskette with software     Other Features   User friendly graphical OSD Menu, eSaver, iMenu and Screen+ Software, ultra low power consumption.     Dimensions (WxHxD mm)   Monitor: 371x299x143, Carton: 423x304x106     Weight   0.87 Kg / 1.92 lbs (Net)     1.50 Kg / 3.31 lbs (gross)   1.50 Kg / 3.31 lbs (gross) </th <th></th> <th></th>		
Vertical: 50 Degrees (CR>10)Scanning FrequencyHorizontal: 30K~60KHz Vertical: 60~70 HzPixel Frequency85.5 MHzMaximum Resolution1366x768@60HzRecommended Resolution1366x768@60HzSupported Resolutions640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1360x720@60Hz, 1366x768@60HzSignal InputAnalog: 0.7Vp-p(standard), 75 OHM, PositiveConnectorsAnalog RGB Signal: 15-pin D-sub MalePower SourceUSB PoweredPower ConsumptionOn: 7 Watts (Max), Standby: <0.5W		
Scanning FrequencyHorizontal: 30K~60KHz Vertical: 60~70 HzPixel Frequency85.5 MHzMaximum Resolution1366x768@60HzRecommended Resolution1366x768@60HzSupported Resolutions640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1360x720@60Hz, 1366x768@60HzSignal InputAnalog: 0.7Vp-p(standard), 75 OHM, PositiveConnectorsAnalog RGB Signal: 15-pin D-sub MalePower SourceUSB PoweredPower ConsumptionOn: 7 Watts (Max), Standby: <0.5W	Viewing Angle	- · · · ·
Vertical: 60~70 HzPixel Frequency85.5 MHzMaximum Resolution1366x768@60HzRecommended Resolution1366x768@60HzSupported Resolutions640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1360x720@60Hz, 1366x768@60HzSignal InputAnalog: 0.7Vp-p(standard), 75 OHM, PositiveConnectorsAnalog RGB Signal: 15-pin D-sub MalePower SourceUSB PoweredPower ConsumptionOn: 7 Watts (Max), Standby: <0.5W		
Pixel Frequency85.5 MHzMaximum Resolution1366x768@60HzRecommended Resolution1366x768@60HzSupported Resolutions640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1360x720@60Hz, 1366x768@60HzSignal InputAnalog: 0.7Vp-p(standard), 75 OHM, PositiveConnectorsAnalog RGB Signal: 15-pin D-sub MalePower SourceUSB PoweredPower ConsumptionOn: 7 Watts (Max), Standby: <0.5WPlug & PlayDDC /2B/CIUser ControlPower OnlyOSD Languages15 Languages including English, French and SpanishRegulationsFCC,CE, RoHS, Energy Star 5.0What's in the boxVGA Cable (S-SUB), USB power cable, Instruction Manual, Guarantee Card and Diskette with softwareOther FeaturesUser friendly graphical OSD Menu, eSaver, iMenu and Screen+ Software, ultra low power consumption.Dimensions (WxHxD mm)Monitor: 371x299x143 , Carton: 423x304x106 0.87 Kg / 1.92 lbs (Net) 1.50 Kg / 3.31 lbs (gross)	Scanning Frequency	
Maximum Resolution1366x768@60HzRecommended Resolution1366x768@60HzSupported Resolutions640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1360x720@60Hz, 1366x768@60HzSignal InputAnalog: 0.7Vp-p(standard), 75 OHM, PositiveConnectorsAnalog RGB Signal: 15-pin D-sub MalePower SourceUSB PoweredPower ConsumptionOn: 7 Watts (Max), Standby: <0.5W		
Recommended Resolution1366x768@60HzSupported Resolutions640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1360x720@60Hz, 1366x768@60HzSignal InputAnalog: 0.7Vp-p(standard), 75 OHM, PositiveConnectorsAnalog RGB Signal: 15-pin D-sub MalePower SourceUSB PoweredPower ConsumptionOn: 7 Watts (Max), Standby: <0.5WPlug & PlayDDC /2B/ClUser ControlPower OnlyOSD Languages15 Languages including English, French and SpanishRegulationsFCC,CE, RoHS, Energy Star 5.0What's in the boxVGA Cable (S-SUB), USB power cable, Instruction Manual, Guarantee Card and Diskette with softwareOther FeaturesUser friendly graphical OSD Menu, eSaver, iMenu and Screen+ Software, ultra low power consumption.Dimensions (WxHxD mm)Monitor: 371x299x143, Carton: 423x304x106 0.87 Kg / 1.92 lbs (Net) 1.50 Kg / 3.31 lbs (gross)		
Supported Resolutions640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1360x720@60Hz, 1366x768@60HzSignal InputAnalog: 0.7Vp-p(standard), 75 OHM, PositiveConnectorsAnalog RGB Signal: 15-pin D-sub MalePower SourceUSB PoweredPower ConsumptionOn: 7 Watts (Max), Standby: <0.5W		-
1360x720@60Hz, 1366x768@60HzSignal InputAnalog: 0.7Vp-p(standard), 75 OHM, PositiveConnectorsAnalog RGB Signal: 15-pin D-sub MalePower SourceUSB PoweredPower ConsumptionOn: 7 Watts (Max), Standby: <0.5W		
Signal InputAnalog: 0.7Vp-p(standard), 75 OHM, PositiveConnectorsAnalog RGB Signal: 15-pin D-sub MalePower SourceUSB PoweredPower ConsumptionOn: 7 Watts (Max), Standby: <0.5W	Supported Resolutions	
ConnectorsAnalog RGB Signal: 15-pin D-sub MalePower SourceUSB PoweredPower ConsumptionOn: 7 Watts (Max), Standby: <0.5W	Circul Innut	
Power SourceUSB PoweredPower ConsumptionOn: 7 Watts (Max), Standby: <0.5W		
Power ConsumptionOn: 7 Watts (Max), Standby: <0.5W	Connectors	Analog RGB Signal: 15-pin D-sub Male
Plug & PlayDDC /2B/CIUser ControlPower OnlyOSD Languages15 Languages including English, French and SpanishRegulationsFCC,CE, RoHS, Energy Star 5.0What's in the boxVGA Cable (S-SUB), USB power cable, Instruction Manual, Guarantee Card and Diskette with softwareOther FeaturesUser friendly graphical OSD Menu, eSaver, iMenu and Screen+ Software, ultra low power consumption.Dimensions (WxHxD mm)Monitor: 371x299x143 , Carton: 423x304x106 0.87 Kg / 1.92 lbs (Net) 1.50 Kg / 3.31 lbs (gross)	Power Source	USB Powered
User ControlPower OnlyOSD Languages15 Languages including English, French and SpanishRegulationsFCC,CE, RoHS, Energy Star 5.0What's in the boxVGA Cable (S-SUB), USB power cable, Instruction Manual, Guarantee Card and Diskette with softwareOther FeaturesUser friendly graphical OSD Menu, eSaver, iMenu and Screen+ Software, ultra low power consumption.Dimensions (WxHxD mm)Monitor: 371x299x143 , Carton: 423x304x106 0.87 Kg / 1.92 lbs (Net) 1.50 Kg / 3.31 lbs (gross)	Power Consumption	
OSD Languages15 Languages including English, French and SpanishRegulationsFCC,CE, RoHS, Energy Star 5.0What's in the boxVGA Cable (S-SUB), USB power cable, Instruction Manual, Guarantee Card and Diskette with softwareOther FeaturesUser friendly graphical OSD Menu, eSaver, iMenu and Screen+ Software, ultra low power consumption.Dimensions (WxHxD mm)Monitor: 371x299x143 , Carton: 423x304x106 0.87 Kg / 1.92 lbs (Net) 1.50 Kg / 3.31 lbs (gross)		
RegulationsFCC,CE, RoHS, Energy Star 5.0What's in the boxVGA Cable (S-SUB), USB power cable, Instruction Manual, Guarantee Card and Diskette with softwareOther FeaturesUser friendly graphical OSD Menu, eSaver, iMenu and Screen+ Software, ultra low power consumption.Dimensions (WxHxD mm)Monitor: 371x299x143 , Carton: 423x304x106 0.87 Kg / 1.92 lbs (Net) 1.50 Kg / 3.31 lbs (gross)		
What's in the boxVGA Cable (S-SUB), USB power cable, Instruction Manual, Guarantee Card and Diskette with softwareOther FeaturesUser friendly graphical OSD Menu, eSaver, iMenu and Screen+ Software, ultra low power consumption.Dimensions (WxHxD mm)Monitor: 371x299x143 , Carton: 423x304x106 0.87 Kg / 1.92 lbs (Net) 1.50 Kg / 3.31 lbs (gross)		
Guarantee Card and Diskette with software       Other Features     User friendly graphical OSD Menu, eSaver, iMenu and Screen+ Software, ultra low power consumption.       Dimensions (WxHxD mm)     Monitor: 371x299x143 , Carton: 423x304x106 0.87 Kg / 1.92 lbs (Net) 1.50 Kg / 3.31 lbs (gross)		
Other FeaturesUser friendly graphical OSD Menu, eSaver, iMenu and Screen+ Software, ultra low power consumption.Dimensions (WxHxD mm)Monitor: 371x299x143 , Carton: 423x304x106 0.87 Kg / 1.92 lbs (Net) 1.50 Kg / 3.31 lbs (gross)	What's in the box	
Dimensions (WxHxD mm)Monitor: 371x299x143 , Carton: 423x304x106Weight0.87 Kg / 1.92 lbs (Net) 1.50 Kg / 3.31 lbs (gross)		
Dimensions (WxHxD mm)     Monitor: 371x299x143 , Carton: 423x304x106       Weight     0.87 Kg / 1.92 lbs (Net)       1.50 Kg / 3.31 lbs (gross)	Other Features	
Weight     0.87 Kg / 1.92 lbs (Net)       1.50 Kg / 3.31 lbs (gross)		Sonware, unra low power consumption.
Weight     0.87 Kg / 1.92 lbs (Net)       1.50 Kg / 3.31 lbs (gross)	Dimensions (WxHxD mm)	Monitor: 371x299x143 , Carton: 423x304x106
1.50 Kg / 3.31 lbs (gross)		
	-	
	Loading Qty w/pallet	
UPC Code 685417062089		