



TL-WR941HP

Gama Superior - Los amplificadores de alta potencia y las antenas de alta ganancia proporcionan un alcance inalámbrico mejorado de hasta 10.000 pies cuadrados.

Wall-Penetrating Wi-Fi - La señal mejorada de Wi-Fi corta a través de paredes y obstáculos, eliminando las zonas muertas

3 Modos Funcionalidad - Ofrece tres modos inalámbricos, incluyendo Router, Range Extender y Access Point

450Mbps Wireless Speed - Ideal para streaming de video, juegos en línea y VoIP

CARACTERÍSTICAS DE HARDWARE

Interfaz	4 10/100Mbps LAN Ports 1 10/100Mbps WAN Port
Botón	Wireless On/Off Button, RE Button, WPS Button Reset Button, Power On/Off Button
Antena	3*9dBi Detachable Omni Directional Antenna (RP-SMA)
Fuente de Alimentación Externa	12VDC / 1.5A
Estándares Inalámbricos	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Dimensiones (W X D X H)	9.0 x 7.5 x 1.9 in. (227.5 x 190 x 48.3mm)

CARACTERÍSTICAS INALÁMBRICAS

Frequency	2.4-2.4835GHz
Signal Rate	11n: Up to 450Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)
Reception Sensitivity	450M: -71dBm@10% PER 130M: -74dBm@10% PER 108M: -74dBm@10% PER 54M: -77dBm@10% PER

CARACTERÍSTICAS INALÁMBRICAS

	11M: -91dBm@8% PER 6M: -89dBm@10% PER 1M: -97dBm@8% PER
Transmit Power	CE:<20dBm(2.4GHz) FCC:<30dBm
Wireless Functions	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Wireless	64/128/152-bit WEP / WPA / WPA2, WPA-PSK / WPA2-PSK

CARACTERÍSTICAS DE SOFTWARE

Quality of Service	WMM, Bandwidth Control
WAN Type	Dynamic IP/Static IP/PPPoE/ PPTP/L2TP/BigPond
Management	Access Control Local Management Remote Management
DHCP	Server, Client, DHCP Client List, Address Reservation
Port Forwarding	Virtual Server, Port Triggering, UPnP, DMZ

CARACTERÍSTICAS DE SOFTWARE

Dynamic DNS	DynDns, Comexe, NO-IP
VPN Pass-Through	PPTP, L2TP, IPSec (ESP Head)
Access Control	Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security	DoS, SPI Firewall IP Address Filter/MAC Address Filter/Domain Filter IP and MAC Address Binding

OTHERS

Certification	CE, FCC, RoHS, NCC, BSMI
Package Contents	450Mbps Wireless N High Power Router RJ45 Ethernet Cable Power Adapter Quick Installation Guide Technical Support Card
System Requirements	Microsoft® Windows 10/8.1/8/7, XP, MAC® OS, NetWare®, UNIX® or Linux.
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

