

## 300Mbps High Power Wireless N Router

### TL-WR841HP

#### ⦿ Features:

- High power amplifier and 5dBi antennas provide 4x the wireless range of a normal router
- Enhanced Wi-Fi signal cuts through walls and obstacles, eliminating dead zones
- 2x the wireless speed of a normal router over long-distances enables seamless data transfer and media streaming across your network
- 300Mbps wireless speed ideal for video streaming, online gaming and VoIP
- Backward compatible with 802.11b/g products
- Easily setup a WPA encrypted secure connection at a push of the WPS button
- Bandwidth control allows administrators to determine how much bandwidth is allotted to each PC
- Parental control allows parents or administrators to establish restricted access policies for children or staff
- Supports virtual server, special application and DMZ host ideal for creating a website within your LAN
- Easy Setup Assistant provides quick & hassle-free installation
- External detachable antennas allow for better alignment and stronger antenna upgrades



#### ⦿ Description:

300Mbps High Power Wireless N Router TL-WR841HP is a powerful wireless solution well suited for the home or office. With 300Mbps wireless speeds, TL-WR841HP is ideal for streaming HD video, making VoIP calls and online gaming. What's more, featured with high power amplifier, 2\*5dBi antennas and high transmission Power, the device greatly boosts Wi-Fi performance.

## Ⓞ Specifications:

HARDWARE FEATURES	
Interface	4 10/100Mbps LAN Ports 1 10/100Mbps WAN Port
Button	WPS/Reset Button
External Power Supply	12VDC / 1A
Wireless Standards	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Antenna	2*5dBi Detachable Omni Directional Antenna (RP-SMA)
Dimensions ( W x D x H )	6.6in.x5.1in.x1.2in.(168.5mmx130mmx31.5mm)
WIRELESS FEATURES	
Frequency	2.4-2.4835GHz
Signal Rate	11n: Up to 300Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)
EIRP	<20dBm (EIRP, For countries using CE Standards) <30dBm (EIRP, For countries using FCC Standards)
Reception Sensitivity	270M: -71dBm@10% PER 130M: -74dBm@10% PER 108M: -74dBm@10% PER 54M: -77dBm@10% PER 11M: -91dBm@8% PER 6M: -89dBm@10% PER 1M: -97dBm@8% PER
Wireless Functions	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Wireless Security	64/128/152-bit WEP / WPA / WPA2,WPA-PSK / WPA2-PSK
SOFTWARE FEATURES	
WAN Type	Dynamic IP/Static IP/PPPoE/ PPTP/L2TP/BigPond
DHCP	Server, Client, DHCP Client List, Address Reservation
Quality of Service	WMM, Bandwidth Control
Port Forwarding	Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS	DynDns, Comexe, NO-IP
VPN Pass-Through	PPTP, L2TP, IPSec (ESP Head)
Access Control	Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security	DoS, SPI Firewall IP Address Filter/MAC Address Filter/Domain Filter IP and MAC Address Binding
Management	Access Control Local Management Remote Management

## ⊙ Specifications:

OTHERS	
Certifications	CE, FCC, RoHS, Wi-Fi
System Requirements	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7, MAC® OS, NetWare®, UNIX® or Linux.
Environment	Operating Temperature: 0°C ~40°C (32°F ~104°F) Storage Temperature: -40°C ~70°C (-40°F ~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

## ⊙ Diagram:



## Package:

- 300Mbps High Power Wireless N Router TL-WR841HP
- 2 Detachable Omni Directional Antennas
- Power supply unit
- Resource CD
- Quick Installation Guide